



2025 Promotion



Add Friends

AS ONE

Lab Equipment



18,500.-

Auto Dry Desiccator
Item no. 1-5486-21
Model OH-3S (220V)



25,500.-

Auto Dry Desiccator
Item no. 1-5488-22 Model
UVOH-520SA (220V)



7,900.-

Desiccator
Item no. 1-001-01
Model LH




32,000.-

Cool Incubator
Item no. 2-926-21
Temp: 3 to 45 °C
Capacity: 28 L (220V)



23,900.-

Gel Electrophoretic
Item no. 1-5484-01
Output: 18 to 135 V
Timer: 0-99 min (220V)



40,900.-

Gel Electrophoretic
Item no. 4-809-01
Wavelength: 470 nm
Max gel size: 100x150 mm



5,090.-

Quartz Cuvette (2ea/box)
Item no. 3-573-02
Volume: 3.5 ml
Optical path distance (mm): 10



1,950.-

Glass Cuvette (2ea/box)
Item no. 3-574-02
Volume: 3.5 ml
Optical path distance (mm): 10



26,900.-

Magnetic Stirrer 4 Position
Item no. 1-4604-42
Speed (rpm): MAX.1500
Stirring capacity (mL): 50 ~ 2000 x 4 (220V)



38,500.-

Magnetic Stirrer 6 Position
Item no. 1-4604-42
Speed (rpm): MAX.1500
Stirring capacity (mL): 50 ~ 2000 x 6 (220V)



800.-

Spray (Autoclavable) 500mL
Item no. 2-7625-01
Disinfection ethanol and reverse soap
can be used.

Clean Room



Contact Us !!

Polyester Clean Wiper
Item no. 1-2261-01
Size: 9 x 9 inches
γ ray sterilized (bulk packaging)
1box(50sheets×15bags)
RoHS3 (EU)2015/863 Certificates



Contact Us !!

Economy Wiper
Item no. 3-1725-01, 02, 03
Material: Polyester 87%, Nylon13%
Size (inch): 4 x 4, 6 x 6, 9 x 9
Quantity:1 bag (600, 150, 150 sheets)
RoHS3 (EU)2015/863 Certificates



Contact Us !!

STERILIZATION CLEANPAPER A4 BLUE
Item no. 2-4940-01
It employs recyclable dust-free paper.
Material: Cellulose, water soluble resin polymer
γ ray sterilized (bulk packaging)
Size: A4, Color: Blue
Quantity: 1 box (250 pieces/bag x 10 bags)
RoHS3 (EU)2015/863 Certificates

หมายเหตุ: ราคายังไม่รวมภาษีมูลค่าเพิ่ม (Vat7%), ยินราคาถึง 31 ธันวาคม 2568 หรือจนกว่าสินค้าจะหมด



2025 Promotion



Add Friends



27,900.-

EC meter model AB23EC W/Electrode
 Conductivity / TDS / Salinity
 EC range: 00.0 µS/cm – 199.9 mS/cm
 Resolution: 0.01 µS/cm
 Accuracy: ± 1 % Reading ± 3 LSD
 Display: LCD with backlight



19,500.-

pH meter model AB23pH W/Electrode
 pH range: 0.00 to 14.00 pH
 Resolution: 0.01 pH
 Accuracy: +/- 0.1 pH
 ORP: +/- 1999 mV
 Temp: 0.0 to 100.0 °C
 Display: 5" segment LCD



45,000.-

pH meter model AB41pH W/Electrode and Stirrer Compact
 pH range: -2.000 to 20.000 pH
 Resolution: 0.1/0.01/0.001 pH
 Accuracy: +/- 0.002 pH
 ORP: +/- 2000.0 mV
 Temp: -10.0 to 125.0 °C
 Display: 6.5" LCD Backlight



35,500.-

Get Free!!
1 block

1 Block Dry Block Heaters Model HB1DG
 Control: Digital
 Temp. Range: Ambient + 5°C – 120°C
 Timer: 1 second - 9999 minutes
 Stability: ± 0.2°C



48,500.-

Get Free!!
2 block

2 Block Dry Block Heaters Model HB1DG
 Control: Digital
 Temp. Range: Ambient + 5°C – 120°C
 Timer: 1 second - 9999 minutes
 Stability: ± 0.2°C



9,990.-

Vortex Mixer model VXMNAL
 Speed: 300 to 2800 rpm
 Touch mode operation
 Continuous mode



Microcentrifuge Tube Blocks

Select block

Brand/Sample Type	Number of Wells	Wells Diameter	Well Depth	Item Number
0.5 mL Tube	30	7.9 mm	27.6 mm	30400157
1.5 mL Tube	20	11.1 mm	39.1 mm	30400159
1.5 mL Eppendorf™ Tube	20	11.5 mm	36.9 mm	30400162
2 mL Eppendorf™ Tube	20	11.5 mm	38.1 mm	30400191
2 mL Corning™ Tube	20	10.9 mm	38.1 mm	30400192



11,500.-

Guardian™ 2000 Hotplates & Stirrers Model e-G21HS07C
 Speed: 200 to 1600 rpm
 Control: Analog
 Capacity: 15 L
 Temp.: 70 to 500 °C

หมายเหตุ: ราคายังไม่รวมภาษีมูลค่าเพิ่ม (Vat7%), ยินราคาถึง 31 ธันวาคม 2568 หรือจนกว่าสินค้าจะหมด

บริษัท แอลเคมีสต์ ไซแอนติฟิค จำกัด (สำนักงานใหญ่)
 300/218 โครงการพาทีไอ พระราม 9-ศรีนครินทร์ ถนนกรุงเทพกรีฑา
 แขวงห้วยหมาก เขตบางกะปิ กรุงเทพมหานคร 10240

Tel: +66 968953750
 Email: cs.alchemist@outlook.com
 Website: www.alchemistscientifichailand.com

Line OA: @sales.alchemist



2025 Promotion



Add Friends

Cole-Parmer®

240,000.-



130-Watt Ultrasonic Processor with Timer and Pulsar Item no.04714-51
Sample Volume: 150 uL to 150 ml
Timer controls: 1s to 10hr.
Included: Probe with tip

370,000.-



แถมฟรี!
ตุ้กับเสียบอะคริลิก
Stand & Clamp
Jiffy Jack

750-Watt Ultrasonic Homogenizer with Temp Controller Item no.04711-45
Sample Volume: 250 uL to 1000 ml
Timer controls: 1s to 10hr.
Included: Probe with tip

49,990.-



Digital Colony Counter with Magnifier Item no. (14212-04+14212-61)
Accept with 50- to 90-mm Petri dishes
bright-white, LED light source
Magnifier 3.0xDIGITAL

22,900.-



HEATING MANTLE, 500 ML
MODEL HM-200-500 Item no. 36002-14
500 mL flask capacity
Max temperature (° C): 450
Chemical resistant PP housing
is "safe to the touch"

24,000.-



HEATING MANTLE, 1000 ML
MODEL HM-200-1000 Item no. 36002-18
1000 mL flask capacity
Max temperature (° C): 450
Chemical resistant PP housing
is "safe to the touch"

35,500.-



GAST DOA-P504-BN VACUUM PUMP
Item no.07061-42
Max Flow Rate (L/min): 28
Max Vacuum (in Hg): 24
Motor hp: 1/8

59,000.-



12-port SPE Manifolds
Item no. 06480-04
included: Lid, PP needles, stopcocks, rack, vacuum gauge, water collection container and plate for accepting 11, 12, 16 mm dia. tube or vial

13,500.-



Pipette Controller OmegaZen
Item no. 25300-96
Accepts glass or plastic serological pipette 1 to 100 mL
Silicone adapter autoclavable
LCD Display

950.- /bottle



pH buffer pH 4, 7, 10
(500 ml/bottles)
Item no.00654-00, -04, -08

1,790.-



Electrode Storage Solution
Item no. 00653-04
Capacity: 500 mL

หมายเหตุ: ราคายังไม่รวมภาษีมูลค่าเพิ่ม (Vat7%), ยินราคาถึง 31 ธันวาคม 2568 หรือจนกว่าสินค้าจะหมด

บริษัท แอลเคมีสต์ ไซแอนติฟิค จำกัด (สำนักงานใหญ่)
300/218 โครงการพาทีไอ พระราม 9-ศรีนครินทร์ ถนนกรุงเทพกรีฑา
แขวงหัวหมาก เขตบางกะปิ กรุงเทพมหานคร 10240

Tel: +66 968953750
Email: cs.alchemist@outlook.com
Website: www.alchemistscientifichailand.com

Line OA: @sales.alchemist



2025 Promotion



Add Friends



3,850.-/EA

VWR® PHP Pipettes are fully autoclavable, High performance pipettes with low plunger force.

- Durable tip ejector made using special corrosion resistant alloy, protecting against chemical & physical corrosion.
- Effortless tip ejection with unique shock absorbing mechanism.
- Fully Autoclavable
- Volume lock
- Calibrated as per ISO 8655-6 in ISO 17025 accredited lab
- Large and clear 4 digit display
- Color coding for easy identification
- Highly durable PVDF tip cone

PHP (PRECISE HIGH PERFORMANCE) PIPETTE

Item no.	Description
VWRA613-6688	PHP – Single Channel Variable Volume PIPETTE 0.1-2.5 µl
VWRA613-6689	PHP – Single Channel Variable Volume PIPETTE 0.5-10 µl
VWRA613-6690	PHP – Single Channel Variable Volume PIPETTE 2-20 µl
VWRA613-6692	PHP – Single Channel Variable Volume PIPETTE 10-100 µl
VWRA613-6693	PHP – Single Channel Variable Volume PIPETTE 20-200 µl
VWRA613-6694	PHP – Single Channel Variable Volume PIPETTE 100-1000 µl
VWRA613-6695	PHP – Single Channel Variable Volume PIPETTE 1000-5000 µl
VWRA613-6696	PHP – Single Channel Variable Volume PIPETTE 1000-10000 µl

หมายเหตุ: ราคายังไม่รวมภาษีมูลค่าเพิ่ม (Vat7%), ยินราคาถึง 31 ธันวาคม 2568 หรือจนกว่าสินค้าจะหมด

บริษัท แอลเคมีสต์ ไซแอนติฟิค จำกัด (สำนักงานใหญ่)
300/218 โครงการพาทีไอ้ พระราม 9-ศรีนครินทร์ ถนนกรุงเทพกรีฑา
แขวงหัวหมาก เขตบางกะปิ กรุงเทพมหานคร 10240

Tel: +66 968953750
Email: cs.alchemist@outlook.com
Website: www.alchemistscientifichailand.com

Line OA: @sales.alchemist



2025 Promotion



Add Friends



BenchMate C8-M Micro Centrifuges
 Rotor Capacity:
 8x1.5/2ml Tube rotor &
 2 Place PCR Strip Rotor
 Speed: 6000 RPM,
 2000xg (MAX RCF)



7,500.-

C12V High-Speed Microcentrifuge
 12-place 1.5 mL/2.0 mL microcentrifuge
 tube rotator included
 Maximum rpm/RCF 15,000 rpm/15,596 x g
 Timer Setting Countdown Timer from 1
 Minute to 999 Minutes



39,900.-



Non-Sterile



Sterile

Syringe Filter			Price	
Material	Pore Size	Diameter	Non-Sterile (100/Box)	Sterile (50/Box)
Nylon	0.22 µm	13 mm	1,590.-	-
		25 mm	1,820.-	2,100.-
	0.45 µm	13 mm	2,000.-	-
		25 mm	1,820.-	2,000.-
PTFE	0.22 µm	13 mm	1,750.-	-
		25 mm	2,290.-	-
	0.45 µm	13 mm	1,750.-	-
		25 mm	2,250.-	-
PES	0.22 µm	13 mm	1,710.-	1,800.-
		25 mm	1,970.-	2,000.-
	0.45 µm	13 mm	1,710.-	1,800.-
		25 mm	1,970.-	2,000.-
CA	5.0 µm	25 mm	2,100.-	-

Micro-Centrifuge Tube With Safe-Lock Cap

Sterile



1.5 ml 2.0 ml 5.0 ml

Volume	Price/Pack	
	1-10 pk	≥ 11 pk
1.5 ml	380.-	300.-
2.0 ml	550.-	490.-
5.0 ml	450.-	430.-

หมายเหตุ 1.5-2.0ml = 500pcs/pk, 5.0ml 200pcs/pk

380.-



Air vent filters (Non-sterile)
 63 mm. (dia.)
 Membrane: PTFE
 Pore Size: 0.2 µm

19,000.-



Vacuum Pump Model V400
 Max Pressure: 100 mbar
 Max flow rate: 34 L/min

หมายเหตุ: ราคายังไม่รวมภาษีมูลค่าเพิ่ม (Vat7%), ยินราคาถึง 31 ธันวาคม 2568 หรือจนกว่าสินค้าจะหมด

บริษัท แอลเคมีสต์ ไซแอนติฟิค จำกัด (สำนักงานใหญ่)
 300/218 โครงการพาทีโอ พระราม 9-ศรีนครินทร์ ถนนกรุงเทพกรีฑา
 แขวงหัวหมาก เขตบางกะปิ กรุงเทพมหานคร 10240

Tel: +66 968953750
 Email: cs.alchemist@outlook.com
 Website: www.alchemistscientifichailand.com

Line OA: @sales.alchemist



2025 Promotion



Add Friends

Serological Pipette



Volume	Price
1 ml (500pcs/case)	3,000.-
2 ml (500pcs/case)	3,300.-
50 ml (100pcs/case)	2,600.-



- Sterile and available individually packed peel-to-open wrap.
- DNase/RNase-, Pyrogenic-
- Compliance with USP Class VI
- Colour-coded for ease of identification.
- Filter barrier to prevent liquid overflow.




Volume	Price
5 ml (200pcs/case)	1,550.-
10 ml (200pcs/case)	1,800.-
25 ml (200pcs/case)	2,300.-
50 ml (100pcs/case)	2,600.-



Centrifuge Tubes with Flat Cap
Sterile, PP Autoclavable
RNase-free, DNase-free, and non-pyrogenic.
Max. rotation speed up to 12500×g

Volume	Price (500pcs/case)
15 ml	4,000.-
50 ml	5,000.-



Sterilized Petri Dish Plastic
90×15 mm

Qty. (Box)	Price (500pairs/case)
1 -10	1,790.-
≥11	1,700.-



Pipette Tips (China)
10 uL, 1000 ea/pk
200 uL, 1000 ea/pk
1000 uL, 500 ea/pk

250.-/pk

Buy 3 Get 1 Free!!

หมายเหตุ: ราคายังไม่รวมภาษีมูลค่าเพิ่ม (Vat7%), ยินราคาถึง 31 ธันวาคม 2568 หรือจนกว่าสิ้นค้าหมด

บริษัท แอลเคมีสต์ ไซแอนติฟิค จำกัด (สำนักงานใหญ่)
300/218 โครงการพาทีไอ พระราม 9-ศรีนครินทร์ ถนนกรุงเทพกรีฑา
แขวงหัวหมาก เขตบางกะปิ กรุงเทพมหานคร 10240

Tel: +66 968953750
Email: cs.alchemist@outlook.com
Website: www.alchemistscientifichailand.com

Line OA: @sales.alchemist



2025 Promotion



Add Friends

MASTERFLEX
part of avantor

Special Offer!!

สายยาง **Masterflex** ทุกรหัสสินค้า

BUY 3 Get 1 Free!!



หมายเหตุ: สินค้าแถมคิดจากสินค้าที่มีมูลค่าต่ำที่สุด
Note: The free product is the item with the lowest value.

L/S Series: Laboratory Peristaltic pumps



- Digital pumps**
- Max rpm: 100 or 600 rpm
 - Flow rate :
0.06 to 580 mL/min (for 100 rpm)
0.006 to 3400 mL/min (for 600 rpm)
 - Pump Head Accepted : 1 to 4
 - Programmable
 - IP33 or 66
 - Real-time pump control and monitoring
 - with MasterflexLive



- Easy Load II (1- or 2- channels)**
- New design automatic tubing retention allow for multiple tubing sizes
 - Rotor is constructed of stainless steel
 - Pump head are stackable for multichannel applications

หมายเหตุ: ราคายังไม่รวมภาษีมูลค่าเพิ่ม (Vat7%), ขึ้นราคาถึง 31 ธันวาคม 2568 หรือจนกว่าสินค้าจะหมด

บริษัท แอลเคมิสต์ ไซแอนติฟิค จำกัด (สำนักงานใหญ่)
300/218 โครงการพาทีไอ พระราม 9-ศรีนครินทร์ ถนนกรุงเทพกรีฑา
แขวงห้วยหมาก เขตบางกะปิ กรุงเทพมหานคร 10240

Tel: +66 968953750
Email: cs.alchemists@outlook.com
Website: www.alchemistscientifichailand.com

Line OA: @sales.alchemist



2025 Promotion



Add Friends

stakpure

The Omnia series is extremely convenient to use. All devices are fitted with the OptiFill one-hand dispenser with integrated control- and monitoring unit.

The Omnia Optifill *touch* dispenser

Intuitive. Convenient. Flexible



New

- Key features:**
- Color touch display with intuitive menu navigation
 - One-Hand Operation Dispenser
 - Pivotable up to 170 degrees
 - USB interface for data transmission/output
 - Real time display of all operating and performance parameters.



- One hand operation
- Easy water dispensing
- Fits neatly on the wall
- Space saving under table

Ultrapure and Pure Water with real-time TOC monitoring

OmniaTap xs^{touch} Blue line is the ideal system when both pure water and ultrapure water are required, but in relatively small amounts.

- Features:**
- OptiFill^{touch} dispenser is standard
 - 7-litres pure water tank
 - Real time TOC monitoring
 - Fully recirculation
 - Leakage sensor is standard
- Water quality:**
- Type II: up to 10-15 MΩxcm
 - Type I : 18.2 MΩxcm

Flow rate:

- Type II: 8 L/hr.
- Type I: up to 2.0 L/min

- 2 different models:**
- OmniaTap XS^{touch} UV-TOC,
 - OmniaTap XS^{touch} UV-TOC/UF



Contact Us !!

GRANT

- T100 0 to 100°C
- TC120 -15 to 120°C
- TX150 -15 to 150°C
- TXF200 -15 to 200°C

Optional: Cooling Accessory

C1G 0 to 40°C



C2G -15 to 40°C



Contact Us !!

Combine with Stainless steel tanks

Stainless steel tanks				
ST5-5L	ST12-12L	ST18-18L	ST26-26L	ST38-38L



หมายเหตุ: ราคายังไม่รวมภาษีมูลค่าเพิ่ม (Vat7%), เป็นราคาถึง 31 ธันวาคม 2568 หรือจนกว่าสินค้าจะหมด

บริษัท แอลเคมิสต์ ไซแอนติฟิค จำกัด (สำนักงานใหญ่)
300/218 โครงการพาทีไอ พระราม 9-ศรีนครินทร์ ถนนกรุงเทพกรีฑา
แขวงหัวหมาก เขตบางกะปิ กรุงเทพมหานคร 10240

Tel: +66 968953750
Email: cs.alchemist@outlook.com
Website: www.alchemistscientifichailand.com

Line OA: @sales.alchemist